## Amendments to the Claims:

This listing will replace all prior versions, and listings, of claims in the application:

## Listing of Claims:

Claim 1 (Currently amended): A hose reel which comprises:

a spool for receiving a length of hose thereon;

a mounting bracket;

a fluid inlet tube having a central axis and coupling the spool to the mounting bracket so that the spool can rotate about the central axis of the fluid inlet tube with respect to the mounting bracket; and

a mechanical rewinding mechanism coupled to the spool,

the spool including a hub assembly and a pair of spool flange plates attached to opposite sides of the hub assembly,

the hub assembly comprising comprising, as an a one-piece, cast or molded integral element thereof, unitary structure that includes:

a latch gear having a plurality of teeth that cooperate with a rewinding latch mechanism. mechanism, and

a substantially cylindrical surface upon which a hose can be wound.

Appl. No. 10/698,720

Arndt. Dated February 8, 2005

Reply to Office Action of November 8, 2004

Claim 2 (Currently amended): A hose reel according to claim 1, wherein the one-piece cast or

molded hub assembly further comprises latch goar assembly is supported on an annular bracing

structure that is an integral element of the hub assembly, upon which the latch gear assembly is

supported.

Claim 3 (Currently amended): A hose reel according to claim 1, wherein the one-piece cast or

molded hub assembly further comprises comprises, as integral elements thereof, a plurality of

radial spokes which support hub sections of the hub assembly.

Claim 4 (Original): A hose reel according to claim 3, wherein the hub sections are spaced apart

circumferentially and connected together by circumferentially extending web structures.

Claim 5 (Original): A hose reel according to claim 1, wherein the mechanical rewinding

mechanism includes a spring housing containing a spiral spring and the hose reel includes a

spring biased pawl which is pivotally coupled to the spring housing and positioned to cooperate

with latch gear.

Claim 6 (Currently amended): A hose reel according to claim 5, wherein the one-piece cast or

molded hub assembly further includes a central hub that includes a spring catch and the spiral

-3-

PAGE 5/15 \* RCVD AT 2/8/2005 5:31:58 PM (Eastern Standard Time) \* SVR:USPTO-EFXRF-1/1 \* DNIS:8729306 \* CSID:734 995 1777 \* DURATION (mm-ss):03-38

spring has an inner end that is configured to engage the spring catch.

Claim 7 (Original): A hose reel according to claim 1, wherein the mechanical rewinding mechanism includes a spring housing and the mounting bracket is coupled to the spring housing.

Claim 8 (Original): A hose reel according to claim 1, further including a hose guide that is coupled to the mounting bracket and includes a through-opening that is framed by plurality of rollers.

Claim 9 (Original): A hose reel according to claim 1, wherein the spool flange plates are attached to opposite sides of the hub assembly by a plurality of mechanical fasteners which extend through each of the spool flange plates with the hub assembly positioned therebetween.

Claim 10 (Currently amended): A <u>one-piece cast or molded</u> hub assembly for a hose recl which comprises, as an <u>a single unitary structure</u>: integral unit:

a central hub;

a plurality of spokes extending radially from the central hub;

a plurality of hub sections provided at the radial ends of the plurality of spokes which define a cylindrical surface upon which a hose can be wound;

an annular bracing element connected between the plurality of spokes; and

a latch gear provided on the annular bracing element.

Claim 11 (Currently amended): A <u>one-piece cast or molded</u> hub assembly for a hose reel according to claim 10, wherein the plurality of hub sections are spaced apart circumferentially and connected together by circumferentially extending web structures.

Claim 12 (Currently amended): A <u>one-piece cast or molded</u> hub assembly for a hose reel according to claim 10, wherein the plurality of spokes are aligned with axially centers of the plurality of hub sections and the annual bracing element, latch gear and central hub all extend from a common axial side of the plurality of spokes.

Claim 13 (Currently amended): A <u>one-piece cast or molded</u> hub assembly for a hose reel according to claim 10, wherein the plurality of spokes each have circumferentially and axially extending bracing support structures.

Claim 14 (Currently amended): A <u>one-piece cast or molded</u> hub assembly for a hose reel according to claim 10, wherein the central hub includes a spring catch.

Claim 15 (Currently amended): A <u>one-piece cast or molded</u> hub assembly for a hose reel according to claim 10, wherein the latch gear includes a plurality of outward projecting teeth.

Claim 16 (Currently amended): A <u>one-piece cast or molded</u> hub assembly for a hose reel according to claim 15, wherein the outward projecting teeth are arranged in at least one segment that includes a group of teeth that are preceded and followed by a recess.

Claim 17 (Currently amended): A <u>one-piece cast or molded</u> hub assembly for a hose reel according to claim 10, wherein the hub assembly comprises an integrally cast unitary structure.

Claim 18 (Currently amended): A method of forming a spool for a hose reel which comprises:

a) providing a <u>one-piece cast or molded</u> hub assembly that comprises <u>as a single unitary</u> structure: an integral unitary structure that includes:

a central hub;

a plurality of spokes extending radially from the central hub;

a plurality of hub sections provided at the radial ends of the plurality of spokes which define a cylindrical surface upon which a hose can be wound; and

a latch gear;

- b) providing a pair of spool flange plates; and
- c) attaching the pair of spool flange plates to opposite sides of the <u>one-piece cast or</u> molded hub assembly.

Claim 19 (Currently amended): A method of forming a spool for a hose reel according to claim 18, wherein the step of attaching the pair of spool flange plate to opposite sides of the one-piece cast or molded hub assembly comprises coupling the spool flange plates together with a plurality of mechanical fasteners with the one-piece cast or molded hub assembly positioned between the pair of spool flange plates.

Claim 20 (Currently amended): A method of forming a spool for a hose reel according to claim 18, which comprises further providing the one-piece cast or molded hub assembly with comprising providing a spring catch in the central hub of the one-piece cast or molded hub assembly.